

**NOTE: The Wedge Mounts in the Center of the Rear Overhead Cross Bar above your head**

**Part #7035 & 7045**

- 1) Install horseshow brackets around the Overhead Cross bar above your head using the #10-32 Screws and washers included mount the Speaker Wedge into the inserts. (Fig.1)
- 2) After the brackets are installed the Wedge will rotate loosely around the bar. **Position to the desired angle. (Fig. 2)**
- 3) Once the wedge is positioned drill 13/64" Hole through bracket hole into the Center Bar. (Fig. 3)
- 4) Using the self-taping screw mount the wedge at your desired angel and screw into place. (Fig. 4)
- 4) Connect the 10' wire harness to the back of the Wedge
- 5) Run Wire harness to desired location.



(Fig. 1)



(Fig. 2)



(Fig. 3)



(Fig. 4)



Close Up Installed on a Ranger



Front View Installed

**WIRING GUIDELINES**

**FOR #7035 & #7045**

- 1) Connecting Speakers:  
Splice wires from the Wedge into the left and right speaker wires under the dash
- |   |   |
|---|---|
| <p><b>Drivers Side - Left</b><br/>Green / Red (+)<br/>Green (-)</p> | <p><b>Passenger Side - Right</b><br/>White /Red (+)<br/>White (-)</p> |
|---|---|

**FOR 7045 with LED Light Show**

NOTE: Not used for #7035 W/O LED Light Show

- 2) Connecting the Power for the LED Light Show  
**LED Light Show**  
Red (+) Attach to Battery or Fuse  
Black(-) Attach to a good ground

**RANGER Brackets & Screws**



Part #71XXB (Fits 1.75" Bar)

Vertically Driven Products  
1401 Freeman Avenue  
Long Beach, CA 90804  
(562) 438-5112  
[info@vdpusa.com](mailto:info@vdpusa.com)