

NOTE: The Wedge Mounts on the Center Plate of the Roll Cage above and behind your head

Part #8035 & #8045

- 1) Place and center the bracket on the rectangle portion on the top cross bar and mark the (4) 1/8" holes to drill.
NOTE: HOLE SIDE IS ON THE TOP - NOT ON THE MOUNTING SIDE
- 2) Drill the (4) 1/8" holes which you marked in step 1. (Fig 2)
- 3) Mount the Bracket using the (4) #10x3/4" Sheet metal screws. (Fig. 3)
- 4) Mount the Wedge Using the (4) #10-32x3/4" Screws and lock washers. Run wire connector through hole
- 4) Connect the 10' wire harness to the back of the Wedge
- 5) Run Wire harness to desired location.

TOP HOLE



(Fig. 1)



(Fig. 2)



(Fig. 3)



Installed on a MULE 3000



(Fig. 4)

WIRING GUIDELINES

FOR #8035 & #8045

- 1) Connecting Speakers:
Splice wires from the Wedge into the left and right speaker wires under the dash
- | | |
|----------------------------|-------------------------------|
| Drivers Side - Left | Passenger Side - Right |
| Green / Red (+) | White /Red (+) |
| Green (-) | White (-) |

FOR 8045 with LED Light Show

NOTE: Not used for #8035 W/O LED Light Show

- 2) Connecting the Power for the LED Light Show
- LED Light Show**
Red (+) Attach to Battery or Fuse
Black (-) Attach to a good ground

MULE 300 Bracket & Screws



- Part #80XXB (4) #10x3/4" Sheet Metal Screw
Mule 3000 (4) #10-32x3/4" Screw
(8) Lock Washers

Vertically Driven Products
1401 Freeman Avenue
Long Beach, CA 90804
(562) 438-5112
info@ydpusa.com